

SK380HDLc

STANDARD EQUIPMENT

ENGINE
Engine, HINO J08E-UN, diesel engine with turbocharger and intercooler
Automatic engine deceleration
Auto Idle Stop (AIS)
Automatic engine shut-down for low engine oil pressure
Engine oil pan drain valve
Double element air cleaner
Pre-air cleaner
CONTROL
Working mode selector (H-mode and S-mode)
Power Boost
SWING SYSTEM & TRAVEL SYSTEM
Swing rebound prevention system
Straight propel system
Two-speed travel with automatic shift down
Grease-type track adjusters
Automatic swing brake
HYDRAULIC
Arm regeneration system
Aluminum hydraulic oil cooler
N&B and N&B piping
MIRRORS & LIGHTS
Two rearview mirrors
Four front working lights
CAB & CONTROL
Two control levers, pilot-operated
Tow eyes
Horn, electric
Integrated left-right slide-type control box
Cab, all-weather sound suppressed type
Cab light (interior)
Coat hook
Luggage tray
Large cup holder
Detachable two-piece floor mat
Double slide seat
7-way adjustable suspension seat
Retractable seatbelt
Headrest
Handrails
Intermittent windshield wiper with double-spray washer
Tinted safety glass
Pull-up type front window and removable lower front window
Easy-to-read multi-display monitor
Automatic air conditioner
Emergency escape hammer

OPTIONAL EQUIPMENT

Travel alarm
Refueling pump
Yellow warning lamp

Note: Standard and optional equipment may vary. Consult your KOBELCO dealer for specifics.

KOBELCO

SK380HDLc-8

Hydraulic Excavators

SK380HDLc

Bucket Capacity:
1.4 - 1.6 m³ ISO heaped
Engine Power:
200 kW/2,100 min⁻¹ (ISO 14396)
Operating Weight:
36,000 kg

Note: This catalog may contain attachments and optional equipment that are not available in your area. And it may contain photographs of machines with specifications that differ from those of machines sold in your areas. Please consult your nearest KOBELCO distributor for those items you require. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice. Copyright by **KOBELCO CONSTRUCTION MACHINERY CO., LTD.** No part of this catalog may be reproduced in any manner without notice.

KOBELCO CONSTRUCTION MACHINERY CO., LTD.

17-1, Higashigotanda 2-chome, Shinagawa-ku, Tokyo 141-8626 JAPAN
Tel: +81 (0) 3-5789-2146 Fax: +81 (0) 3-5789-2135
www.kobelco-kenki.co.jp/english_index.html

Inquiries To:

We Save You Fuel
Achieving a Low-Carbon Society

The Concept of Beautiful Performance

The Power Wave of Change

When we set out to design our new hydraulic excavators, we kept our eyes on the big picture. Of course we wanted machines with greater digging capacity. But they also had to be fuel-efficient and economical, while imposing less of a burden on the local and global environments. Applying our advanced technologies, we developed KOBELCO's new SK380HDL, an entirely new kind of excavator that beautifully balances all the demands of today's construction industry. Lean and efficient with capacity to spare, these sleek powerhouses bring a whole new style to the worksite while setting new standards for environmental responsibility.



- Sturdy Construction & Built-in Durability ▶
- Efficient Performance ▶
- Easy Maintenance ▶
- Comfort and Safety ▶



Pursuing the "Three E's"

The Perfection of Next-Generation, Network Performance

Enhancement

- Greater Performance Capacity
- New hydraulic circuitry minimizes pressure loss
 - High-efficiency, electronically controlled Common Rail Fuel Injection Engine
 - Powerful travel and arm/bucket digging force
 - Sturdy Construction

Economy

- Improved Cost Efficiency
- Advanced power plant that reduces fuel consumption
 - Easy maintenance that reduces upkeep costs
 - High structural durability and reliability that retain machine value longer

Environment

- Features That Go Easy on the Earth
- Auto Idle Stop as standard equipment
 - Noise reduction measures (with improvement of the sound quality) minimize noise and vibration

Sturdy Construction & Built-in Durability


Stable Attachment Strength

Forged and cast components are used throughout. The arm tip's cross-sectional coefficient is 15 % higher than previous models, giving the arm the same strength as the 3-faced reinforced arm that was offered only as an option before. The strength of the boom foot has also been increased by 18 %.


Durability That Retains Machine Value Five and Ten Years in the Future

- New operator's seat covered in durable material
- High-quality urethane paint
- Easily repaired bolted hand rails

Reinforced arm foot pin




Integrated cast steel boom top



Reinforced boom




Cast steel boom foot boss




Pre-air Cleaner

The pre-air cleaner prolongs a replacement cycle of main air cleaner.



Forged steel arm foot boss



Reinforced arm with rock guard




Thicker shoe plate



Reinforced idler



Extra heavy-duty idler cover



Reinforced track guides installed on three places



Stronger casing for travel motor




Reinforced travel motor cover

Emergency Acceleration (Dial) Permits Continued Operation in the Unlikely Event of Malfunction



If unexpected trouble is experienced with the ITCS mechatronic control system, the machine can still be operated using the emergency acceleration system. Digging modes are also automatically relayed to an emergency system so that digging can continue temporarily until a service person arrives to repair the primary system.



Newly designed MCU



New MCU Conventional MCU

- Vertical alignment and sealed cover gives better protection from water and dust
- Integration in base plate boosts assembly quality
- Reliable fixture to base plate



Countermeasures Against Electrical System Failure

All elements of the electrical system, including controller, have been designed for enhanced reliability.



Efficient Performance



Amazing Productivity with 18 % Saving in Fuel Consumption and Top-Class Cost Performance

	Fuel Consumption* 18% improvement in fuel efficiency when performing more work volume (S-Mode)
	Work Volume* 27% increase in work volume using the same amount of fuel. (H-Mode)



“Top-Class” Powerful Digging

Max. arm crowding force:	165kN	
Max. arm crowding force with power boost:	181kN	
Max. bucket digging force:	222kN	
Max. bucket digging force with power boost:	244kN	

Powerful Travel

Travel torque: increased by	13%	
Drawbar pulling force:	322kN	

Greater Swing Power, Shorter Cycle Times


Swing torque: increased by	7%	
Swing speed:	10.0min⁻¹	

Significant Extension of Continuous Working Hours

The combination of large-capacity fuel tank and excellent efficiency delivers an impressive 22 % increase in continuous operation hours.**

Fuel tank:	22%	
------------	------------	---

Light Lever Operation



It takes 10% less effort to move the control levers, so that operators can work longer hours with less fatigue.

10%Less


*The value shows results from actual measurements taken by KOBELCO when compared with previous KOBELCO models.
**The value shows results from actual measurements taken by KOBELCO for continuous operation in S Mode, compared with previous models.
Results vary depending on the method of operation and load conditions.



NEXT-3E Technology

New Hydraulic System

Rigorous inspections for pressure loss are performed on all components of the hydraulic piping, from the spool of the control valve to the connectors. This regimen, combined with the use of a new, high-efficiency pump, cuts energy loss to a minimum.



NEXT-3E Technology

Next-Generation Electronic Engine Control

The high-pressure, common-rail fuel-injection engine features adjustable control to maximize fuel efficiency and provide powerful medium/low-speed torque. The result is a highly fuel-efficient engine.



NEXT-3E Technology

Total Tuning Through Advanced ITCS Control

The next-generation engine control is governed by a new version of ITCS, which responds quickly to sudden changes in hydraulic load to ensure that the engine runs as efficiently as possible with a minimum of wasted output.

ITCS (Intelligent Total Control System) is an advanced, computerized system that provides comprehensive control of all machine functions.

Simple Select: Two Digging Modes


H Mode	For heavy duty when a higher performance level is required.
S Mode	For normal operations with lower fuel consumption.

N&B (crusher and breaker)

The operator selects the desired mode from inside the cab, and the selector valve automatically configures the machine accordingly.




Auto Idle Stop Provided as Standard Equipment



This function saves fuel and cuts emissions by shutting down the engine automatically when the safety lock lever is pulled up. It also stops the hourmeter, which helps to retain the machine's asset value.

Automatic Acceleration/Deceleration Function Reduces Engine Speed

Engine speed is automatically reduced when the control lever is placed in neutral, effectively saving fuel and reducing noise and exhaust emissions. The engine proportionally comes to desire speed when the lever is moved out of neutral.



Easy Maintenance

Comfortable "On the Ground" Maintenance




The machine layout was designed with easy inspection and maintenance in mind.

Access Through the Left Side Cover

Parallel Cooling Units Are Easy to Clean

Large-capacity radiator and oil cooler are aligned side by side, with intercooler positioned in front. This more effective layout gives outstanding cooling results.



Oil cooler
Radiator
Air conditioner condenser
Intercooler condenser

Quick Oil Drain Valves for Quick Maintenance



Quick drain valve



Fuel drain valve

More Efficient Maintenance



Detachable two-piece floor mat with handles for easy removal.



Easy-access fuse box.



Air conditioner filter can be easily removed.



Hour meter can be checked while standing on the ground.



Large-capacity tool box.


Pre-air Cleaner

The pre-air cleaner prolongs a replacement cycle of main air cleaner.



Access Through the Right Side Cover

The fuel filter with built-in water separator functions in two ways by removing large contaminants and separating out water.



Main fuel filter
Pre-fuel filter (with built-in water separators)



Main fuel filter

Highly Durable Filter

The high-capacity hydraulic oil filter incorporates glass fiber with superior cleaning power and durability. With a replacement cycle of 1,000 hours and a construction that allows replacement of the filter element only, it's both highly effective and highly economical.



Double-Element Air Cleaner as Standard



The large-capacity element features a double-filter structure that keeps the engine running clean even in dusty environments.

Air cleaner (double element)

Monitor Display with Essential Information for Accurate Maintenance Checks



- Displays only the maintenance information that's needed, when it's needed.
- Self-diagnostic function that provides early-warning detection and display of electrical system malfunctions.
- Record previous breakdowns, including irregular and transient malfunctions.

Choice of 16 Languages for Monitor Display



With messages including those requiring urgent action displayed in the local language, users in all parts of the world can work with greater peace of mind.

Comfort and Safety

Spacious, Comfortable Cab

Designed for safety, the cab meets ISO standards, and also offers a spacious interior and plenty of foot room, with levers and other controls ideally positioned for easy operation.

- A long wiper covers a wide area for a broad view in bad weather.
- Back mirrors provide a safe view of the rear.
- Reinforced green glass windows meet European standards.

Wide-Access Cab Ensures Smooth Entry and Exit



The left control box lifts up with the safety lock lever to add 10° to the cab entry angle for easy entrance and exit.



Plenty of Foot Room

The rigid cab construction and liquid-filled viscous cab mounts minimize cab vibration. In addition, the use of new lower rollers on the crawlers cuts travel vibration in half compared with previous models.

In-Cab Noise is Reduced by 3dB Compared with Previous Models.

Newly Designed Information Display Prioritizes Visual Recognition



The analog gauge provides information that's easy to read regardless of the operating environment. The information display screen has been enlarged, and a visor is attached to further enhance visibility.

Suspension Seat

Comfortable, double-sliding suspension seat, fitted as standard, creates a higher grade working environment and reduces fatigue.



Creating a Comfortable Operating Environment



Seat can be reclined to horizontal position



Double slide seat



Powerful automatic air conditioner




Spacious luggage tray



One-touch lock release simplifies opening and closing the front window



Large cup holder



• New interior design and materials create an elegant feel

Low Noise Level and Mild Sound Quality

The electronically controlled common-rail engine has a unique fuel injection system that runs quietly.

Meets EMC (Electromagnetic Compatibility) Standards in Europe.

Measures have been taken to ensure that the SK machines do not cause electro-magnetic interference.

Bracket for Attaching a Head Guard Provided as Standard Equipment

A bracket is provided as standard equipment that allows the optional head guard to be simply bolted on.

Automatic Engine Shut-Down for Low Engine Oil Pressure

Safety Features That Take Various Scenarios into Consideration



Firewall separates the pump compartment from the engine



Hammer for emergency exit

- Thermal guard prevents contact with hot components during engine inspections
- Hand rails meet European standards
- Retractable seatbelt requires no manual adjustment



Engine

Model	HINO J08E-UN
Type:	Direct injection, water-cooled, 4-cycle diesel engine with turbocharger, intercooler
No. of cylinders:	6
Bore and stroke:	112 mm X 130 mm
Displacement:	7.684 L
Rated power output:	188 kW /2,100 min ⁻¹ (ISO9249) 200 kW /2,100 min ⁻¹ (ISO14396)
Max. torque:	969 N·m/1,600 min ⁻¹ (ISO9249) 998 N·m/1,600 min ⁻¹ (ISO14396)



Hydraulic System

Pump	
Type:	Two variable displacement pumps + 1 gear pump
Max. discharge flow:	2 X 294 L/min, 1 X 20 L/min
Relief valve setting	
Boom, arm and bucket:	34.3 MPa {350 kgf/cm²}
Power Boost:	37.8 MPa {385 kgf/cm²}
Travel circuit:	34.3 MPa {350 kgf/cm²}
Swing circuit:	29.0 MPa {296 kgf/cm²}
Control circuit:	5.0 MPa {50 kgf/cm²}
Pilot control pump:	Gear type
Main control valves:	8-spool
Oil cooler:	Air cooled type



Swing System

Swing motor:	Axial-piston motor
Brake:	Hydraulic; locking automatically when the swing control lever is in the neutral position
Parking brake:	Hydraulic disc brake
Swing speed:	10.0 min ⁻¹ {rpm}
Tail swing radius:	3,650 mm
Min. front swing radius:	4,370 mm



Attachments

Backhoe bucket and arm combination

Use			Backhoe bucket	
			Normal digging	
Bucket capacity	ISO heaped	m³	1.4	1.6
	Struck	m³	1.0	1.2
Opening width	With side cutter	mm	1,460	1,650
	Without side cutter	mm	1,250	1,440
No. of bucket teeth			5	5
Bucket weight			1,410	1,450
Combinations	2.6 m short arm		○	◎
	3.3 m standard arm		◎	×

◎ Standard ○ Recommended × Not recommended



Travel System

Travel motors:	2 X axial-piston, two-step motors
Travel brakes:	Hydraulic brake per motor
Parking brakes:	Oil disc brake per motor
Travel shoes:	48 each side
Travel speed:	5.6/3.3 km/h
Drawbar pulling force:	322 kN (ISO7464)
Gradeability:	70 % {35°}
Ground clearance:	500 mm



Cab & Control

Cab
All-weather, sound-suppressed steel cab mounted on the silicon-sealed viscous mounts and equipped with a heavy, insulated floor mat.
Control
Two hand levers and two foot pedals for travel
Two hand levers for excavating and swing
Electric rotary-type engine throttle



Boom, Arm & Bucket

Boom cylinders:	140 mm X 1,550 mm
Arm cylinder:	170 mm X 1,788 mm
Bucket cylinder:	150 mm X 1,193 mm



Refilling Capacities & Lubrications

Fuel tank:	580 L
Cooling system:	31.1 L
Engine oil:	28.5 L
Travel reduction gear:	2 X 9.5 L
Swing reduction gear:	7.4 L
Hydraulic oil tank:	280 L tank oil level
	353 L hydraulic system



Working Ranges

		Unit: m	
Boom		6.5 m	
Range	Arm	Short 2.6 m	Standard 3.3 m
a - Max. digging reach		10.61	11.26
b - Max. digging reach at ground level		10.4	11.06
c - Max. digging depth		6.86	7.56
d - Max. digging height		10.26	10.58
e - Max. dumping clearance		7.06	7.37
f - Min. dumping clearance		3.32	2.62
g - Max. vertical wall digging depth		5.84	6.61
h - Min. swing radius		4.45	4.37
i - Horizontal digging stroke at ground level		4.21	5.82
j - Digging depth for 2.4 m (8') flat bottom		6.67	7.4
Bucket capacity ISO heaped m³		1.6	1.4



		Unit: kN (tf)	
Arm length		Short 2.6 m	Standard 3.3 m
Bucket digging force		221	222
		244*	244*
Arm crowding force		205	165
		225*	181*

*Power Boost engaged.



Dimensions


Arm length	Short 2.6 m	Standard 3.3 m
A Overall length	11,430	11,350
B Overall height (to top of boom)	3,640	3,420
C Overall width	3,200	
D Overall height (to top of cab)	3,160	
E Ground clearance of rear end*	1,190	
F Ground clearance*	500	



Operating Weight & Ground Pressure











In standard trim, with 6.5 m boom, 3.3 m standard arm, and 1.4 m³ ISO heaped bucket















Shaped		Triple grouser shoes (even height)	
Shoe width	mm	600	
Overall width	mm	3,200	
Ground pressure	kPa	67	
Operating weight	kg	36,000	



A - Reach from swing centerline to arm top
B - Arm top height above/below ground
C - Lifting capacities in kilograms

- Max. discharge pressure: 34.3 MPa (350 kg/cm²)

SK380HDLCLC		Short Arm: 2.6 m Bucket: Without Shoe: 600 mm										
A B		3.0 m		4.5 m		6.0 m		7.5 m		At Max. Reach		Radius
												
7.5 m	kg									*7,750	*7,750	7.06 m
6.0 m	kg					*8,310	*8,310	*7,610	7,520	*7,540	6,720	8.00 m
4.5 m	kg			*11,960	*11,960	*9,280	*9,280	*7,980	7,290	*7,510	5,860	8.58 m
3.0 m	kg					*10,420	9,570	*8,530	6,980	*7,580	5,430	8.87 m
1.5 m	kg					*11,320	9,070	*9,010	6,710	*7,710	5,290	8.89 m
G. L.	kg			*15,780	13,220	*11,700	8,800	*9,230	6,530	*7,870	5,410	8.66 m
-1.5 m	kg	*13,910	*13,910	*14,970	13,280	*11,430	8,740	*8,970	6,500	*8,010	5,870	8.15 m
-3.0 m	kg	*16,900	*16,900	*13,350	13,350	*10,350	8,890			*8,020	6,910	7.29 m
-4.5 m	kg	*12,780	*12,780	*10,320	*10,320					*7,530	*7,530	5.95 m

SK380HDL		Standard Arm: 3.3 m Bucket: Without Shoe: 600 mm															
A	B	1.5 m		3.0 m		4.5 m		6.0 m		7.5 m		9.0 m		At. Max. reach		Radius	
																	
9.0 m	kg														*5,710	*5,710	6.56 m
7.5 m	kg									*6,910	*6,910				*5,230	*5,230	7.86 m
6.0 m	kg									*7,020	*7,020				*5,050	*5,050	8.71 m
4.5 m	kg							*8,620	*8,620	*7,510	7,230	*6,930	5,380		*5,050	*5,050	9.25 m
3.0 m	kg					*13,420	*13,420	*9,900	9,550	*8,170	6,900	*7,200	5,230		*5,220	4,770	9.52 m
1.5 m	kg					*15,380	13,410	*11,020	8,990	*8,800	6,590	*7,490	5,070		*5,550	4,650	9.54 m
G. L.	kg					*16,050	12,960	*11,680	8,630	*9,210	6,370	*7,620	4,960		*6,120	4,730	9.33 m
1.5 m	kg			*13,910	*13,910	*15,730	12,870	*11,740	8,490	*9,220	6,270				*7,080	5,050	8.85 m
-3.0 m	kg	*15,840	*15,840	*19,800	*19,800	*14,540	13,010	*11,070	8,530	*8,570	6,320				*7,620	5,770	8.07 m
-4.5 m	kg			*16,120	*16,120	*12,220	*12,220	*9,270	8,780						*7,530	7,340	6.88 m

- Notes:**
- Do not attempt to lift or hold any load that is greater than these lift capacities at their specified lift point radius and heights. Weight of all accessories must be deducted from the above lift capacities.
 - Lift capacities are based on machine standing on level, firm, and uniform ground. User must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, experience of personnel, etc.
 - Arm top defined as lift point.
 - The above lifting capacities are in compliance with ISO 10567. They do not exceed 87% of hydraulic lifting capacity or 75% of tipping load. Lifting capacities marked with an asterisk (*) are limited by hydraulic capacity rather than tipping load.
 - Operator should be fully acquainted with the Operator's and Maintenance Instructions before operating this machine. Rules for safe operation of equipment should be adhered to at all times.
 - Lift capacities apply to only machine as originally manufactured and normally equipped by KOBELCO CONSTRUCTION MACHINERY CO., LTD.