

# KOBELCO

SK28SR-6/SK30SR-6/SK35SR-6

**SK28SR SK30SR SK35SR**




***We Save You Fuel***  
Achieving a Low-Carbon Society

# Full-Size Performance, Short-Radius Agility and Quiet Operation

## COMPACT YET TOUGH MINI

The new KOBELCO SK28SR, SK30SR and SK35SR expand the horizons of mini excavators, and offer practical performance features while maintaining a short tail swing. The new Energy Conservation Mode saves even more fuel, and Kobelco's proprietary iNDR Cooling System ensures quiet operation, protection from dust, and easy maintenance. For greater operator comfort and safety, the spacious cab design offers plenty of room and an unobstructed view. It all adds up to enhanced full-size performance, short-radius agility and a low-noise environment, with exceptional performance features and a full range of value-added functions.







## iNDr Cooling System





The highly airtight engine compartment and the offset duct contribute to noise reduction. The iNDr filter fitted in front of the cooling system ensures easy cleaning. The iNDr system on the SR Series mini excavators features air intake at the front of the machine and air exhaust underneath. It functions in the same way as the iNDr System on the SR series machines.

### Ultimate Low Noise

KOBELCO's exclusive iNDr Cooling System delivers amazingly quiet operation.

Sound Power Level




### Visual Checking and Easy Cleaning

Because the iNDr filter removes dust from the intake air, cooling components stay dirt-free and do not require regular cleaning. The iNDr filter itself can be easily removed and cleaned without the use of tools.



### iNDr Filter

The stainless-steel filter is extremely effective against dust, with 30-mesh wave-type screen that removes tiny dust particles from the intake air.



•30-mesh means that there are 30 holes formed by horizontal and vertical wires in every square inch of filter.

### iNDr Filter Blocks Out Dust

Outside air goes directly from the intake duct through the iNDr filter for dust removal.




## PERFORMANCE

# Compact, yet, Big Performance

### Wide Working Range

A larger boom and arm are provided as standard equipment to ensure a wider working range.



### Short Tail Swing

The compact tail swing improves operating efficiency in limited space.

Tail overhang:  
**0 mm**  
(without rear view mirror)



### Easy Transportability

With an overall height of 2,510 mm, the machine is designed for easy transport.



### Easy Hydraulic Piping for Quick Hitch (Option)

Piping for quick Hitch is useful for changing attachment.



## Fuel Economy and Digging Power


### Solid Digging Performance

#### Assured Pump Flow and Pump Pressure

Pump flow of 38.4 L/min for SK30SR and SK35SR and 28.8 L/min for SK28SR, and pressure of 23.0 MPa (relief valve setting), maintain ample power.

#### Integrated-Flow Pump System

The instant the machine begins to dig extra output from the third pump (which otherwise powers the swing and dozer circuit) is directed to the arm circuit and boom circuit (raise) for added power. This ensures fast and smooth arm and boom raising operation even under heavy loads.



#### Energy Conservation Mode

The machine equipped with S mode, which lowers fuel consumption by up to 25 % over previous models.



#### One Touch Deceleration

The machine features one-touch deceleration. It allows easy switching to an idling state, reducing the fuel consumption while the machine is at rest. The deceleration select switch is provided on the control panel.



Deceleration select switch

### Travel Power

#### Large Capacity Travel Torque

The large capacity travel torque enables the machine to perform spin turn in low mode even when the dozer is pushing a heavy load.

#### Automatic Two-Speed Travel

An automatic shift function ensures smoother, more efficient travel on worksite. When the High mode is selected, the travel system will automatically shift to Low mode whenever the load or climbing grades requires more power.

#### Travel Switch

The travel lever is fitted with a button for easy shift up.



### Powerful and Efficient Dozer Performance

#### Dozer-Blade Shape

KOBELCO's unique blade design solves this problem by forming the earth into an arc that always falls forward. Because this prevents earth from falling behind the blade, only "one pass" is needed.



#### Hydraulic Pilot-Controlled Dozer Operation Lever



The dozer lever features hydraulic pilot control for precise handling.





## MAINTENANCE

# Easy Daily Maintenance

Start-up checks are essential for safe and reliable machine operation. All start-up checks can be performed at ground level, with an easy-to-understand layout and cover design that simplify access and save time.

### Easy Access to Component Inside the Cab



Two-piece floor mats for easy washing



Hour meter



Air conditioner filter



### Floor Mat with Raised Edges

Floor mat's raised edges help keep the cab floor free of mud, simplifying cleaning.



### Easy Access to Cooling Unit

iNDr filter



### Easy Access to Engine Compartment



High-grade fuel filter



Pre fuel filter with built-in water separator



Air cleaner



Fuel tank



## COMFORT

# Comfortable Work Environment

### Spacious Work Environment

The spacious cab provides optimized control layout for comfortable, easy operation. A greater window area further improves visibility. A clear view is provided at the rear, and there's also more floor space, with a seat that slides further to ensure plenty of leg room.

### Easy Access

A wide-opening door and a left-hand tilting control console with safety lever that rises high, make it easy for operators to enter and exit the cab.



*\*Switches on operation levers are for European market.*

### Sliding Door

Sliding door makes cab entry and exit easier where space is tight.



### Reclining Suspension Seat

Suspension seat reclines to allow operator to optimize operating position and sit comfortably.



### Skylight



### Proportional hand control lever for Rotation & N&B piping (option)



Precise proportional controls are integrated into the joystick for ease of operation.

### Color Multi Display (Option)



Operation data as well as the full range of machine-status data can readily be checked.



Maintenance



Working hours



## Comfortable Operating Environment

### Opening Right Window

Rear window to the right can be opened to improve ventilation.



### Climate Control

The climate control system is located down and to the right of the seat keeping the rear view clear.



### Opening/Closing Front Window

The front window features gas damper cylinders for smooth and easy opening and closing.



### Coat Hook



### Room Light



### Two-Speaker FM/AM Radio with Station Select

#### Bluetooth Installed Radio



Bluetooth installed to allow connections with iPhones and other devices.

### 12V Power Source

Power for various purposes



### USB Port

USB port can be used to play music etc.



## Operator Safety

### Reliable Cab/Canopy Structure

The high-strength cab/canopy meets ROPS and TOP GUARD LEVEL 1 standards for greater operator safety.



### Rear Under Mirror



### Rear View Mirror



### Hammer for Emergency Exit



### Bracket for Yellow Rotating Light

Bracket provided at cab rear for optional fitting of a yellow rotating warning light.



### Work Light

Work light is mounted under the boom to protect from damage.



## RELIABILITY

# Reliable Construction

The boom, arm and swing bracket all have large cross-section segments for added attachment strength.

**Boom cylinder cover**



**Forged boom top**




**Plate type pin**



**Bolt-tightened pins**

Bolt-tightened pins firmly lock the boom and arm to prevent the boom top from opening laterally.



**Swing bracket**

Large, thick cast-iron swing bracket/front bracket.



**Hydraulic hosing**

The hydraulic hosing is housed inside the swing bracket.



**Dozer Blade**

Box construction dozer supports provide greater strength.



**Bucket**

Cast-iron idler link provide greater strength.

## Accumulator for Emergency Attachment Lowering

An installed accumulator allows the attachment to be safely lowered to the ground using in-cab controls in the event of an unexpected engine shut-down and class leading smooth operation.


## SPECIFICATIONS

MODEL			SK28SR	SK30SR	SK35SR
Type			SK28SR-6	SK30SR-6	SK35SR-6
Machine Mass	Cab	kg	2,950	3,380	3,770
	Canopy	kg	2,800	3,220	3,630
Bucket Capacity		m³	0.08	0.09	0.11
Bucket Width (with side cutter)		mm	500	500	600
Arm Length		mm	1.18	1.32	1.37
Bucket Digging Force		kN	24.7	27.7	27.8
Arm Crowding Force		kN	16.6	19.1	22.4
ENGINE					
Model			YANMAR 3TNV82A-B		
Type			Water cooled, 4-cycle, 3-cylinder, direct injection, diesel engine		
Power Output	(ISO 9249)	kW/min <sup>-1</sup>	17.1/2,400		
	(ISO 14396)	kW/min <sup>-1</sup>	17.8/2,400		
Max.Torque	(ISO 9249)	N-m/min <sup>-1</sup>	77.7/1,440		
	(ISO 14396)	N-m/min <sup>-1</sup>	79.4/1,440		
Displacement		L	1.331		
Fuel Tank		L	42.0		
HYDRAULIC SYSTEM					
Pump			Two variable displacement pumps + One gear pump		
Max. Discharge Flow		L/min	2 x 28.8, 1 x 16.1		2 x 38.4, 1 x 19.2
Relief Valve Setting		MPa	23.0		
Hydraulic Oil Tank (system)		L	20.4 (41.1)		20.4 (44.8)
TRAVEL SYSTEM					
Travel Motors			2 x axial-piston, two-step motors		
Parking Brake			Oil disc brake per motor		
Travel Speed (high/low)		km/h	3.8/2.1		4.4/2.5
Gradeability		% (degree)	58 (30)		
Drawbar Pulling Force	Cab	kN	34.8	38.3	38.1
	Canopy	kN	34.9	38.4	38.2
CRAWLER					
Shoe			Rubber		
Shoe Width		mm	300		
Ground Pressure	Cab	kPa	26.3	30.1	33.5
	Canopy	kPa	24.9	28.7	32.2
DOZER BLADE					
Width x Height		mm	1,550 x 345	1,550 x 345	1,700 x 345
SWING SYSTEM					
Swing Motor			Axial piston motor		
Parking Brake			Oil disc brake, hydraulic operated automatically		
Swing Speed		min <sup>-1</sup>	8.4		


Unit: mm

MODEL	SK28SR	SK30SR	SK35SR
		CAB Canopy	CAB Canopy
Arm length	1.18m	1.32m	1.37m
a Max. digging reach	4,840 (4,890)	5,200 (5,240)	5,350 (5,390)
b Max. digging reach at ground level	4,680 (4,730)	5,040 (5,080)	5,200 (5,240)
c Max. digging depth	2,590 (2,590)	2,820 (2,830)	2,800 (2,780)
d Max. digging height	4,480 (4,620)	4,800 (4,910)	5,050 (5,150)
e Max. dumping clearance	3,090 (3,210)	3,420 (3,510)	3,640 (3,730)
f Min. dumping clearance	1,290 (1,330)	1,300 (1,320)	1,430 (1,470)
g Max. vertical digging depth	2,270 (2,410)	2,360 (2,510)	2,370 (2,510)
h Min. swing radius at boom straight	2,190 (2,330)	2,300 (2,430)	2,190 (2,310)
h' Min. swing radius at boom swing	1,900 (2,040)	1,910 (2,030)	1,810 (1,920)
i Horizontal Digging stroke at ground level	1,910 (1,810)	2,230 (2,140)	2,400 (2,320)
j Dozer blade (Up/Down)	450/370	470/300	

\*Figures in ( ) show the value when Quick hitch piping installed.




## GENERAL DIMENSIONS



Unit: mm

MODEL	SK28SR	SK30SR	SK35SR
A Overall length	4,510 (4,550)	4,730 (4,760)	4,820 (4,870)
B Overall height	2,510	2,510	2,510
C Overall width	1,550	1,550	1,700
D Tail swing radius	775	775	850
E Tumbler distance	1,700	1,700	1,700
F Overall length of crawler	2,160	2,160	2,160
G Track gauge	1,250	1,250	1,400
H Shoe width	300	300	300
I Overall width of upperstructure	1,530	1,530	1,530
J Distance from dozer top to center of upperstructure	1,500	1,560	1,560
K Ground clearance of rear end	570	570	570
L Ground clearance	300	300	300



MODEL	SK28SR	SK30SR	SK35SR
M Offset volume (Left)	680	720	720
N Offset volume (Right)	675	725	725
O Offset volume between center of boom and center of machine	50	50	50
P Digging volume at outside of shoe (Left)	100	150	120
Q Digging volume at outside of shoe (Right)	200	250	225
R Boom swing angle (Left/Right)	60°/55°	70°/60°	70°/60°

\*Figures in ( ) show the value when Quick hitch piping installed.




## OPTIONAL EQUIPMENT

• Canopy (TOPS/FOPS I)	• Additional counterweight (+250kg)	• Arm and bucket cylinder cover
• Canopy (TOPS/FOPS I) + work light	• Rear view mirror	• 0.05m <sup>3</sup> bucket (W 350mm)
• 300mm steel shoe	• Rear under mirror	• 0.07m <sup>3</sup> bucket (W 450mm)
• Bolt on rubber pad shoe	• Front Guard	• 0.09m <sup>3</sup> bucket (W 500mm)
• Long arm (1.67m)	• Top Guard (only with Cabin)	• 0.11m <sup>3</sup> bucket (W 600mm)
• Rotation (PHC*) & N&B piping (foot control)	• Travel alarm	• 0.12m <sup>3</sup> bucket (W 700mm, only for SK35SR-6)
• Quick Hitch piping	• Multi-Color Display	

\*Proportional Hand Controlled



# LIFT CAPACITIES



A: Reach from swing centerline to arm top  
B: Arm top height above/below ground  
C: Lift capacities in kilograms  
Bucket: Without bucket Dozer blade: up  
Relief valve setting: 23.0 MPa

SK28SR Cab		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK28SR Cab		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK30SR Cab		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK30SR Cab		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK35SR Cab		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK35SR Cab		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

## Notes:

- Do not attempt to lift or hold any load that is greater than these lift capacities at their specified lift point radius and heights. Weight of all accessories must be deducted from the above lift capacities.
- Lift capacities are based on machine standing on level, firm, and uniform ground. User must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, experience of personnel, etc.
- Arm top pin is defined as lift point.

Note: This catalogue may contain attachments and optional equipment that are not available in your area. And it may contain photographs of machines with specifications that differ from those of machines sold in your areas. Please consult your nearest KOBELCO distributor for those items you require. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice.

Copyright by **KOBELCO CONSTRUCTION MACHINERY CO., LTD.** No part of this catalogue may be reproduced in any manner without notice.

## Kobelco Construction Machinery Europe B.V.

Veluwezoom 15  
1327 AE Almere  
The Netherlands  
www.kobelco-europe.com

SK28SR Canopy		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK28SR Canopy		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK30SR Canopy		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK30SR Canopy		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK35SR Canopy		Standard Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

SK35SR Canopy		Long Arm		Bucket: without		Standard weight		Shoe: 300 mm		At Max. Reach		Radius
B	A	1.0 m	2.0 m	3.0 m	4.0 m	5.0 m	6.0 m	7.0 m	8.0 m	9.0 m	10.0 m	
		kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
4.0 m	kg											
3.0 m	kg											
2.0 m	kg											
1.0 m	kg											
G. L.	kg											
-1.0 m	kg											
-2.0 m	kg											

- The above lift capacities are in compliance with ISO 10567. They do not exceed 87% of hydraulic lift capacity or 75% of tipping load. Lift capacities marked with an asterisk (\*) are limited by hydraulic capacity rather than tipping load.
- Operator should be fully acquainted with the Operator's and Maintenance Instructions before operating this machine. Rules for safe operation of equipment should be adhered to at all times.
- Lift capacities apply to only machine as originally manufactured and normally equipped by KOBELCO CONSTRUCTION MACHINERY CO., LTD.

Enquiries To: